

GU

MS-3 P1
oś schodów
między
podstawą
stożka a
górną stożka
w pochyleniu
1:1.5

12060

11.820

SK 1

100

MS-3/S19/5

R1

P1

4+054,79

141.48
3ST-9

141.48
3ST-8

141.48
3ST-7

141.48
3ST-6

141.48
3ST-5

141.48
3ST-4

141.48
3ST-3

141.48
3ST-2

141.48
3ST-1

P1-os-9
141.48

133.60
3ST-20

133.60
3ST-21

133.60
3ST-22

133.60
3ST-23

133.60
3ST-24


133.60
3ST-25

133.60
3ST-26

133.60
3ST-27

133.60
3ST-28

P1-os-d
133.60



4+178,19

1000

200

MS-3 P4
oś schodów
między
podstawą
stożka a
górną stożka
w pochyleniu
1:1.5

90 SK 2

12050

MS-3/S19/5-8

DYLP

KBM k

KBAL

133.33
3ST-46

133.33
3ST-45

133.33
3ST-44

133.33
3ST-43

133.33
3ST-42

133.33
3ST-41

133.33
P4-os-4

133.33
3ST-40

141.36
3ST-38
141.36
3ST-37
141.36
3ST-36
141.36
3ST-35
141.36
3ST-34
141.36
3ST-33
141.36
3ST-32
141.36

P4-os-9
141.36

141.36
3ST-39

141.36
3ST-31